



LockMaster SR2™

Generated on 01.11.2018

Detailed description

CLD LockMaster SR2™ gates are a high security product with accreditation to LPS 1175. All hinges are anti lift off type and fully adjustable. A high security anti drill dead lock is standard on all LockMaster SR2™ gates and the lock is easily accessible from both sides. The gates are supplied with steel drop bolts which are lockable in the open position. A variety of toppings are available for the LockMaster range including standard barbed and razor wire. More sophisticated anti-climb rotating spikes are also available to order. All LockMaster SR2™ gates have a purpose-made lock box with a security key guard – a very secure solution for fence lines, compounds and secure storage.

Features:

- High security.
- Double or single leaf opening.
- Double sided locking.

Applications:

- Government buildings.
- Data centres.
- Airports and seaports.
- Utility suppliers.

Product guidance - As Standard

Mesh:

Securus SR rated.

Posts

LockMaster SR2™ posts are provided in manufacturer standard sizes to accommodate ground conditions:

- Single: 80 x 80 x 5 to 250 x 250 x 6.3 mm SHS.
- Double: 150 x 150 x 5 to 250 x 250 x 6.3 mm SHS.

Options

Gate width:

- Single: 0.9–3.0 m.
- Double: 1.2–6.0 m.

Posts:

CLD Fencing Systems



CLD Fencing Systems
Unit 11
Springvale Business Centre
Millbuck Way
Sandbach
Cheshire
CW11 3HY

Tel: +44 (0)1270 764751

www.cld-fencing.com
sales@cld-fencing.com



Other purpose-made variations are available:

- Base plated posts.
- Straight extensions to gate frame for barbed or razor wire.

Colour and finish:

Hot dipped galvanized and polyester powder-coated green RAL 6005 as standard. Full spectrum of colours available subject to quantity and price.

Locking mechanism:

A large and varied range of access control options are additionally available to complement the range of fence systems and gates. Contact manufacturer for details.

Product specification

Manufacturer

- Name: CLD Fencing Systems
- Web: www.cld-fencing.com
- Email: sales@cld-fencing.com
- Tel: +44 (0)1270 764751
- Fax: +44 (0)1270 757503
- Address: Unit 11, Springvale Business Centre, Millbuck Way, Sandbach, Cheshire CW11 3HY

Product reference	LockMaster SR2™ Security Swing Gate
Type	Double Single
Gate width	[]
Colour and finish	Galvanized and polyester powder coated, RAL - Full RAL range of colours available.
Locking mechanism	London Line Mico PK
Anti-intruder security topping	None Anti-climb rotating spike Barbed wire Razor wire, coiled Saw-tooth edge